SERIE 6

For tractors 75-110 hp

Professional

SERIE 6	
A (mm)	2.280
B (mm)	2.900
C (mm)	3.300
D (mm)	3.300
E (mm)	310



SERIE 6

Digging depth mm	2.900
Rotation angle	180°
Moving frame width mm	1.700
Weight kg	730
Oil tank L	45
Standard bucket mm	300 (30 l)
Tooth tearing resistance kg	2.600
Digging force with auxiliary boom kg	2.100

Technical features and standard equipment

- Sideshifting backhoe with hydraulic locking, applicable to the three-point hitch of the hydraulic boom
- 180° central rotation by 1 cylinder (patented)
- Independent hydraulic stabilisers with block valves
- Independent system with 16 cm³/rev., pump, multiplier, 45-lt built-in tank, oil strainer and hydraulic oil
- Element distributor with 60 lt/min flow rate and finger-tip control levers and built-in shock-absorbing anti-cavitation valves
- Flow rate 25 l/min
- Max working pressure: 190 bar
- Standard bucket: 300 mm
- Boom locking tensioners
- Joints with pins and bushes of case-hardened and tempered steel
- Chrome-plated double-liner cylinder rods
- Sanding and polyester powder coating
- Stiffening tractor frame category 1 and 2

Accessories on request

- Installation 1: auger, grab, multipurpose fork
- Installation 2: hydraulic hammer, ditch cleaning titling buckets 45°, hydraulic rotator + multipurpose fork or Grab (installation 1 included)
- Installation 3: hydraulic mulcher (installation 2 included)
- Hydraulic mulcher 800 mm T1 80 REV
- Remote control on the cab
- Skid steer loader application
- Hitch coupler for articulated backhoe-loaders, backhoe loaders, telescopic loaders

Stiffening tractor frame
Category 1 and 2 - Included

Terminal tools

In replacement of the standard bucket

BUCKET

250 mm
300 mm
400 mm
500 mm
600 mm
700 mm

DITCH CLEANING BUCKET

800 mm
1000 mm
1200 mm

45° TITLING BUCKET

1000 mm
1200 mm

TRAPEZOIDAL BUCKET

740 mm

GRAB

175 dm³

MULTIPURPOSE FORK

800 mm

HYDRAULIC ROTATOR

BR35

HYDRAULIC HAMMER

96 kg

AUGER

TR2

DRILL BITS (Ø x lg.1000 mm)

150
200
250
300
400